

CLAIMS

late
all

1 1. A hand power tool, comprising a housing; at least one
2 handle having at least one gripping part; at least one elastic, vibration-
3 damping element; a mounting part mounted on said elastic element; a said
4 gripping part being mounted on said housing through said elastic element
5 and through said mounting element; and at least one movable safety
6 element through which said gripping part is connected with said mounting
7 part.

1 2. A hand power tool as defined in claim 1, wherein said safety
2 element is formed as a bendable part.

1 3. A hand power tool as defined in claim 2, wherein said safety
2 element is formed as a rope.

1 4. A hand power tool as defined in claim 1, wherein said safety
2 element is formed as a rigid component which is connected through said
3 elastic element with said gripping part and said mounting part.

1 5. A hand power tool as defined in claim 1, wherein said elastic
2 element surrounds said safety element.

1 6. A hand power tool as defined in claim 4, wherein said safety
2 element is arranged in said elastic element along a central axis.

1 7. A hand power tool as defined in claim 1, wherein said safety
2 element in a mounted condition is loaded by pulling, and said elastic element
3 in a mounted condition is loaded by pressure.

1 *cond*
2

8. A hand power tool as defined in claim 1, wherein said safety
element is formed as a band which surrounds said elastic element.

1 *sub*
2 *2*

9. A hand power tool as defined in claim 1, wherein said safety
element determines a maximum deviation of said elastic element from a
base position in a direction selected from the group consisting of a tilting
direction, a displacing direction, and both.

Add c37

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100